



Application

- MOST IMPORTANT STEPS FOR USING **GLAZE GUARD**
 1. Any wax finish must be removed by chemical stripper
 2. The ceramic and grout must be thoroughly cleaned with an appropriate tile cleaner such as CT-50.
 3. Apply the cleaner to the floor and scrub with a recommended nylon grit brush
 4. Allow 15 minutes for the substrate cleaner to begin to breakdown mineral deposits and soiling.
 5. Flood the floor with water and extract with a wet vac.
 6. The floor must be cleaned and rinsed thoroughly to ensure that it is pH neutral. Allow the floor, particularly the grout joints to dry a minimum of 3 hours
 7. Just prior to sealer application vacuum up all the dust. Use a microfiber floor cloth to pick up any final dust and dirt.
 8. Stir Part A until smooth consistency. Pour Part A into mixing container and add Part B while mixing. Mix slowly for 2 minutes, then add Reducer and mix for 1 more minute. The Glaze Guard product is now ready to use.
 9. Use all mixed material within 90minutes
 10. Place mixed product into a roller tray. For best results use roller tray to dip from.
 11. Roller applied coating. Use a NON SHED ¼ inch nap roller. Use 4 or 6" Hot Dog rollers for the edges. To remove fur from roller before use, roll up and down on tacky side of blue tape.
 12. Do not starve the roller of product 12 to 16 sq ft per dip. When rolling out the material do not push down too hard. Use the weight of the roller to roll out any roller lines. Overlap and maintain wet edge (white)
 13. **To avoid missed spots on the floor, make sure the room well lit. Use floor lamps if necessary.**
 14. The product will dry in about 12 hours. Temperature, humidity and environmental conditions can impact this.



CoverTec
innovative chemistry for substrate solutions

1/4 " NAP Shed Resistant Professional Roller Covers –

For the flooring contractors and other various coating jobs requiring minimum linting!
Made with high quality white fabric nap cover.
Shed-resistant.



10857 NW 50 St. Sunrise, FL 33351 • T: 754.223.2465 • F: 754.223.2467
E: tec@covertecproducts.com • www.covertecproducts.com