

Application

- MOST IMPORTANT STEPS WHEN USING **VINYLGUARD**
 1. All finish on Existing floors must be either Stripped or Cleansed with **SurfaceTreat**
 2. New floors can be cleaned with **GlossClean** or similar neutral cleaner
 3. Allow the floor to dry and then use a microfiber mop to pick up any final dust and dirt
 4. If floors are stripped use **PrimeSeal** as a primer/sealer coat before application of the VinylGuard. This will help with self-leveling increase the overall durability of the system and allow for significant time savings during any future stripping process. Apply PrimeSeal, with a flat-mop, at a spread rate of 1200-1500 sq.ft/gal. Dry time is 20 to 30 minutes.
 5. Mix part A **VinylGuard** separately for 1 minute until it is cream color and uniform consistency. Add B side to the A and mix for another 1 minute. **Add the Reducer and mix. Once the Reducer is mixed in the product is ready to use.**
 6. **Place mixed product into a roller tray. For best results use roller tray to dip from.**
 7. Roller apply VinylGuard coating. Use a non shed 1/4 inch nap roller. Roll up and down on blue tape to remove fur. Use 4 or 6" Hot Dog rollers for the edges.
 8. **Do not starve the roller of product 12 to 16 sq. ft. per dip. The product is self-leveling so do not roll too hard. Overlap 2" to 6" and maintain wet edge (white).**
 9. **One gal VinylGuard should cover approx. 500 sq.ft in a single coat.**
 10. **To avoid missed spots on the floor, make sure the room well lit.**
 11. **Change out the roller every 60 minutes.**
 12. Make sure air can circulate to remove moisture from the product.
 13. VinylGuard will dry in about 12 hours. Temperature, humidity and environmental conditions can impact this.
 14. Chair bottoms – use protective bottoms to insure success





1/4 " NAP Shed Resistant Professional Roller Covers –

For the flooring contractors and other various coating jobs requiring minimum linting!
Made with high quality white fabric nap cover.
Shed-resistant.



10821 NW 50 St. Sunrise, FL 33351 • T: 754.223.2465 • F: 754.223.2467
E: tec@covertecproducts.com • www.covertecproducts.com