



CT-FloorStrip HP

Labor saving high performance floor finish stripper

Product Description

CT-FloorStrip HP is a highly effective labor saving stripper that virtually eliminates the need for floor machines, pads, and rinsing. It will solubilize aged and built-up finishes and waxes almost instantly. This high performance floor stripper is designed to remove floor finish, water-based coatings and sealers from heavily burnished floors. May be used as a no-scrub floor stripper or with a conventional floor machine and pad depending on the condition of the floor. Can be sprayed on cove moldings to soften and remove accumulations of old finishes and wax.

Features

- Penetrates multiple layers of floor finish
- Fast floor stripping action
- No odor
- Biodegradable
- Saves time and labor
- Eliminates the need for floor machines
- Highly effective on heavy build up

Main Uses

- Ceramic tile
- Vinyl (VCT)
- Terrazzo
- Flagstone
- Wood and concrete
- Commercial
- Institutional
- Educational
- Industrial

Typical Properties

Property	Typical Results
pH in concentrate	12.7
Odor	None
Specific Gravity at 77°F	1.1
Water solubility	100%
Rinsing	Free rinsing
Biodegradable	Yes
Appearance	Clear liquid.

Packaging

5 gallon (19 liter) pail and 1 gallon (3.8 liter) jug.

Shelf Life

12 months when stored at 77°F (25°C) or less in a dry and shaded area.

Coverage

On average, 1 gallon of FloorStrip HP diluted at 1:4 will cover approximately 500 square feet.

Directions

The desired concentration will depend on the build-up and age of the polish film. As a starting point dilute with warm water as follows:

FOR AVERAGE BUILD-UPS: Dilute 1 to 4 with water.

FOR MODERATE BUILD-UPS: Dilute 1 to 3 with water.

FOR HEAVY AGED BUILD-UPS: Dilute 1 to 2 with water.

FOR USE WITH A FLOOR MACHINE: Dilute 1 to 8-16 parts water. Mop a generous solution onto the floor to be stripped. Allow solution to stand about 5 minutes keeping the floor wet at all times. If mop stripping then agitate with the mop. If using an automatic scrubber or rotary floor machine, no mop agitation is required. Pick-up the solution with a wet vacuum, automatic scrubber or clean mop. Rinse with freshwater and allow floor to dry thoroughly prior to applying any sealer or finish.

Limitations

Do not apply below 40°F (5°C)

Do not use on surfaces that can be harmed by water

Health and Safety

CAUTION: May cause eye irritation.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID: In case of eye contact, immediately flush eyes with plenty of water for at least 15 minutes. Then remove contact lenses if applicable. If irritation persists, get medical attention.

Before using this product consult the Material Safety Data Sheet (MSDS). The MSDS can be obtained at www.covertecproducts.com

Limited Warranty

This product is warranted to be of good quality and that it complies with the properties shown in its current datasheet. CoverTec will replace or, at our election, refund the purchase price of the product if proven defective when used according to the instructions in the current datasheet. Any suspected defect must be reported to CoverTec in writing within one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. CoverTec Products LLC, **makes no warranty as to the merchantability or fitness for a particular purpose and this warranty is in lieu of all other warranties express or implied and explicitly excludes liability for consequential damages, down time, or delay.**