



# CoverShield<sup>®</sup> VS1 Cleaning & Maintenance Instructions

## Daily Maintenance

The most critical procedure for keeping the floor clean is to AGITATE the floor with Neutral Cleaning solution diluted with water using a white pad or soft brush followed by EXTRACTION. The agitation suspends the soil in the water/cleaning solution and the extraction removes the soil from the flooring surface. Removal of the soil prevents it from settling back onto the floor. The AGITATION can be done in many ways including:

- 1) manually with soft brush or
- 2) with a 175-RPM floor machine with a soft brush or white pad or
- 3) by employing an auto scrubber with soft brushes or pads. Use a soft brush manually or with a floor machine to clean

**CoverShield VS1 with CoverGrip.** DO NOT CLEAN VS1/ CoverGrip System WITH A PAD, AS IT WILL MORE QUICKLY WEAR OFF THE COVERGRIP AGGEGATE

**EXTRACTION** should immediately follow agitation. Extraction can be done in many ways including:

- 1) a high quality, commercial wet vac with squeegee or wand or
- 2) an auto scrubber or
- 3) a portable or truck mounted rinse and reclaim system.

## CoverShield VS1<sup>®</sup> Maintenance Tips

1. It is good practice to use Floor Mats at entrance ways to keep dirt and sand to a minimum.
2. Clean the entire flooring surface with a dust mop, as frequently as possible to reduce the amount of sand or other abrasive particles that the wear the coating surface.
3. Always dilute cleaning solutions according to directions, overuse of detergents can leave a residual film on the floor.
4. Take care not to use overly aggressive pads or brushes otherwise you risk dulling and or scratching the surface.
5. Do not over-wet floor; this will avoid leaving 'slop marks' on walls, furniture, carpeting, etc.
6. Always read product label and MSDS before using this or any chemical products for proper use, and any recommended personal protective equipment (PPE) such as glasses, gloves, etc.

**CoverShield® VS1 Maintenance Instructions Continued**

**Deep Cleaning**

**Use SurfaceTreat for Deep cleaning CoverShield VS1 without stripping** Dilute 8fl.oz per 1 gallon of cold water. Use a heavy-duty hair pad under a low speed machine or automatic scrubber to deeply cleanse the finish (will not strip finish). Clean up to 4 layers deep. Scrub floor and pick up the solution in one pass or damp-mop thoroughly. Let it dry. Apply 2 coats of VS1.

**Repair Instructions.**

**To repair high stress areas:** Such as in front of elevators, entrance ways and between check - out counters. Use **SurfaceTreat** diluted 50% with water in a quart spray bottle with a high speed burnisher and pad. Adjust trigger sprayer to a mist . Spray in front of the machine as you walk slowly forward in a straight line. 2 sprays every 2 steps. Walk back over the same area. Let surface dry. Apply 2 coats of VS1.

END OF SECTION

---

