



Surface PrepWork

Efflorescence, rust, and concrete etcher

Product Description

Surface PrepWork is a specially formulated, non-regulated liquid agent for brick, concrete, and tile surfaces. It quickly and safely removes mortar smear, embedded oil and dirt, rust and efflorescence without damaging nearby surfaces. PrepWork can also be used to safely etch bare concrete before applying coatings or sealers. It is 100% biodegradable, non-corrosive, non-regulated, and non-irritating to skin.

Features

- Dissolves Rust and Oxides
- Dissolves Mortar Quickly and Efficiently
- Removes Efflorescence
- Micro etches bare concrete
- OSHA Compliant
- DOT Classification: Not Regulated
- Non-Fuming
- Up to 10 times more effective than other industry products when dissolving Calcium Carbonate

Main Uses

Surface cleaning and preparation of:

- Interlocking concrete pavers
- Bare concrete floors
- Exposed aggregate concrete
- Concrete retaining walls
- Masonry brick
- Mexican tile - Saltillo
- Quarry Tiles
- Ceramic and porcelain
- Cement Terrazzo
- Hard water stains
- Efflorescence
- Grout Haze
- Mineral deposits

Packaging

32 FL. oz (0.95 L) and 1-gallon (3.8L) bottles.

Shelf Life

24 months in unopened container. **Do not allow to freeze.**

Coverage

1 Diluted Gallon of **PrepWork** will cover up to 200 sq. ft. depending upon porosity of surface.

Product Properties

Property	Typical Results
Specific gravity	1.02
pH at 68 deg F	< 1
Water solubility	100%
Biodegradable	100%
odor	mild
Appearance	Clear amber liquid

Application

PrepWork can be used on the job without any neutralization. Depending on build-up to be removed, PrepWork can be diluted with up to 5 parts water.

Always prewet the surface to be cleaned. Apply PrepWork thoroughly to the area to be cleaned. Use a low-pressure garden sprayer, mop or masonry brush. Let stand for approximately 5 minutes. If surface starts to dry out mist with water to keep surface wet for minimum 5 minutes. Rinse thoroughly. Water should be easily absorbed into the concrete. Repeat if necessary.

Recommended dilution PrepWork: Water

Pavers: 1 part: 4 parts water

Broom finished concrete: 1 part: 2 parts water

Concrete Block: 1 part: 4 parts water

Trowel finished concrete: 1 part: 5 parts water

Scrubbing with a stiff brush may be necessary to remove heavy deposits of efflorescence or cement scale.

Allow the floor to dry before applying any subsequent floors sealer.

Health and Safety

Before using this product consult the Material Safety Data Sheet (SDS). The SDS can be obtained at www.covertecproducts.com

Limited Warranty

This product is warranted to be of good quality and that it complies with the properties shown in its current datasheet. CoverTec will replace or, at our election, refund the purchase price of the product if proven defective when used according to the instructions in the current datasheet. Any suspected defect must be reported to CoverTec in writing within one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. CoverTec Products LLC, **makes no warranty as to the merchantability or fitness for a particular purpose and this warranty is in lieu of all other warranties express or implied and explicitly excludes liability for consequential damages, down time, or delay.**